

PRESSURE TRANSMITTERS FOR LIQUID AND GASEOUS MEDIA

SHD 692

see page 2





SHD-SD see page 3

04.24

www.SplusS.de

SHD 692-92 301-4121-0510-68

0 5

DIFFERENTIAL PRESSURE TRANSDUCER PREMASGARD® SHD 692

The **SHD-692** differential pressure transducer is used in piping and hydraulic systems, in mechanical and plant engineering as well as in facility automation. Not suitable for ammonia and freon!



FIND OUT MORE www.SplusS.de

Screw pipe connection for 6 mm pipe (G ¹/₈" - 27 NPT internal thread)

SHD 692 LCD with display

SHD 692

starting at

363,38 €



646,76 €

PRESSURE MEASURING TRANSDUCER PREMASGARD® SHD/SHD-SD



SHD

SHD LCD with display

max. O...40 Bar relative, 4...20mA/0-10V, G½", Steel measuring cell, Water pressure/ Gases Pressure measuring transducer

max. 0...40 Bar relative, 4...20mA/0-10V, G1/2", Steel measuring cell, Water pressure/ Gases Pressure measuring transducer





2



The **PREM**ASGARD[®] SHD pressure transmitter measures relative pressures in the bar range. It converts the measurand into a standard signal of O-10 V or 4...20 mA. Process connection is G 1/2" straight external pipe thread.



FIND OUT MORE www.SplusS.de

SHD-SD

max. 0...40 Bar relative, 4...20mA/0-10V, G1/2", Ceramic measuring cell, Water pressure/ Gases Pressure measuring transducer Not suitable for ammonia and freons



51,94 €



DIFFERENTIAL PRESSURE SWITCH/CONTROLLER **PREM**ASREG[®] **DS**



PRESSURE, DIFFERENTIAL PRESSURE AND VOLUME FLOW MEASURING TRANSDUCERS PREMASGARD[®] 2111





The **PREM**ASREG[®] DS-2 mechanical differential pressure switch/monitor with 4-hole plastic base ring is used for monitoring above-atmospheric, differential and below-atmospheric pressure of clean air, gaseous, nonaggressive media in air ducts, air intake or exhaust devices.

Multipack 40 pieces

(without connection set ASD-06) starting at **23,81 €/pc**.



FIND OUT MORE www.SplusS.de

The calibratable compact pressure transmitters of the **PREM**ASGARD® 211x series are equipped with 8 switchable measuring ranges, 2 switchable output signals (16 devices in one), with or without display, and are used for measuring aboveatmospheric, belowatmospheric, or differential pressures and volume flow in air.



FIND OUT MORE www.SplusS.de

HUMIDIFICATION / DEHUMIDIFICATION

The **HYGR**ASREG® **LS** leakage/ water ingress detector with leakage location serves to detect ingress of water and conductive liquids. It has been designed for early water leakage detection to protect sensitive electrical and electronic equipment in buildings against humidity.



FIND OUT MORE www.SplusS.de

Leakage sensor/water ingress detector HYGRASREG® LS-2/LS-4



Condensation control switch HYGRASREG® KW



Duct hygrostat

HYGRASREG® KH-40W LCD



Room hygro-thermostat HYGRASREG® RHT-30



On-wall hygrostat HYGRASREG® AH-40W LCD







HUMIDITY IN FOCUS





Room hygro-thermostat HYGRASREG® RHT-30W LCD

554







S+S always offers a selection of different measuring devices at special offer prices. Our proven quality products are in stock for you in Nuremberg and are ready for immediate use! Inform yourself directly and secure great discounts on selected products. Tested and certified quality at sale prices - Made in Germany, including a 5-year warranty.



7

SALE



S+S REGELTECHNIK GmbH Thurn-und-Taxis-Str. 22 90411 Nuremberg/Germany

Tel. +49 (0) 911 / 5 19 47-0 mail@SplusS.de Prices by S+S are understood plus legal value added tax at the respective rate in effect. All information provided without prejudice, technical modifications and price changes reserved. Reprints, even excerpts, are only permitted with the approval of S+S Regeltechnik GmbH.

You can find technical data and further information in our catalogue or web shop.



www.SplusS.de